

ADR 2000 PLUS Portable Meter

Peek Traffic Corporation

The Peek ADR 2000 Plus is an autonomous and automatic vehicle counter/classifier. It can be used as a portable or semi-permanent unit.



Description

In its basic configuration, the ADR 2000 Plus operates with 2 or 4 available road tubes. With optional internal sensor modules, it can monitor up to 42 inputs using a combination of WIM, loop, piezos or contact inputs.

The ADR 2000 Plus measures several parameters, including vehicle speed, length, gap and headway. It can then combine them in different data configuration types, including per vehicle records, per lane data and binned vehicle classification by axle. Vehicles may be classified according to the FHWA's "F" scheme or user-defined classification criteria.

The counter is enclosed in a rugged, weather-proof, locking cast aluminium housing that protects it from the elements and ensures a long operating life.

It is equipped with a smart keypad as well as a 20-character x 4-line LCD display. Full operational control can be granted remotely via telemetry or directly in the field via a computer with the appropriate software.

The Peek TOPS and Viper software can be used to collect and analyze the data generated by the Peek ADR Plus.

Specifications

Components

- LCD display: 20 characters x 4 lines
- Inputs: up to 42 sensor inputs plus 4 weather-proof tube inputs
- Battery: 6 volts, 12 amp-hour rechargeable, maintenance free, lead gel, protected by an automatic disconnect at 5.7 volts (separate battery compartment)
- Communications: selectable RS-232 serial rates (300 to 19,200 bps)

- Internal memory: 2 MB

Options

- Up to 24 loop inputs, 24 piezo inputs, 48 contact inputs
- 24 WIM inputs
- SD memory card socket
- Solar power

Operating features

- U.S. or metric units
- Auto daylight saving time
- Compatible with AxleLight® laser sensor
- Compliance with ISO9000 standard
- Compliance with NEMA TS 2 standard for operating conditions and surge (lightning) protection

Technical features

- Counter rate: 200 counts per second per input
- Study period: 24, 48 or 72 hours, 7 days or continuous
- Capacity: approximately 3,280 days of volume data
- Operating temperature range: -40°C to +74°C (-40°F to +165°F)
- Dimensions: 162 mm (H) x 242 mm (W) x 332 mm (D) (6.5 x 9.5 x 13")
- Weight: less than 8 kg (17.6 lb) with battery

For more information: 1 800 363-5913

Created on 09.08.2025 at 09:41:51 EDT